

 Roller · Brush · Spray unit Application	 high hiding power Wall & ceiling interior	 4–6 h recoatable*	 +8 to +25 °C Application	 Water-based · washable Clean with water
---	---	---	--	---

*Surface-dry/recoatable after 4–6 h at 20–25 °C / 40–60 % relative humidity.

CAIRCON Latex paint is a washable and extremely hard-wearing latex paint for interiors: water beads off and dirt can be washed off effortlessly (not fully waterproof). Ideal for heavily used rooms — commercial premises, hospitals, schools, playrooms/children's rooms, hallways, stairwells, bathrooms and kitchens. It is abrasion-resistant, easy to clean, high-hiding, odour-neutral and low-emission — suitable as a final coat for walls and ceilings as well as on plasterboard, gypsum, textured, woodchip and glass-fibre wallpaper and for overcoating old emulsion coatings.

IMPORTANT — CHECK THE COLOUR: Check the colour **BEFORE** application with a test coat — after application, complaint and exchange are excluded. Only work contiguous areas with material from the same delivery / batch number; this also applies to touch-ups.

1 · PREPARE THE SUBSTRATE

1	Clean the surfaces The surfaces to be painted must be clean, dry, dust- and grease-free as well as firm and sound. Completely remove loose dirt, flaking and chalking old coatings, distemper paints, cement laitance, lime deposits, oxide layers, release agents and non-adhering wallpaper.
2	Pre-treat Lightly sand glossy old coatings or pre-treat with a degreasing cleaner. Pre-treat sanding substrates with Deep penetrating primer . Fill cracks, holes and defects with the Levelling compound .

For third-party products used in substrate preparation: check compatibility and final result beforehand on a test area — we accept no liability for the result obtained with third-party products.

2 · APPLY THE LATEX PAINT

3	Prepare the paint Latex paint is ready to use; thinning with water is possible but not recommended. Stir thoroughly before use.
4	Application Apply slowly and crosswise for an even coat. Use a roller, brush or paint spray unit; moisten roller/brush slightly with water. For the spray unit, thin the paint with 5–10 % water (depending on the unit's performance).
5	Clean the tools Clean tools with warm water and soap.

TEST COAT: On critical or already coated substrates, apply a test area beforehand and check adhesion, covering appearance and colour after drying.

TROCKENZEITEN

4–6 h SURFACE-DRY	4–6 h RECOATABLE	approx. 8 days FULLY CURED
-----------------------------	----------------------------	--------------------------------------

Surface-dry/recoatable after 4–6 h.

Do not apply below +8 °C / above +25 °C and above 70 % relative humidity; also do not fall below +8 °C during curing (approx. 8 days).

PRODUCT DATA (GUIDE VALUES)

Base	latex dispersion (water-based), washable, odour-neutral, low-emission
Application area	walls & ceilings interior · plasterboard, gypsum, textured/woodchip/glass-fibre wallpaper, old emulsion coatings
Application	roller, brush or spray unit · +8 to +25 °C, relative humidity max. 70 %
Thinning	ready to use · when spraying 5–10 % water, otherwise optionally max. 10 %
Drying time	surface-dry/recoatable after 4–6 h
Tool cleaning	warm water and soap
Storage	approx. 24 months unopened at +5 to +25 °C, protected from frost and moisture

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS	
Cleaning	Etching solution · Special pre-cleaner
Substrate	Deep penetrating primer · Levelling compound
Tools	Floor roller · Paintbrush set
Similar products	Elephant skin · Floor coating · Wood paint

SAFETY & DISPOSAL	
Labelling	no hazard pictograms · no signal word · no hazard statements — not subject to labelling under CLP
EUH208	Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
P101 / P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
P260	Do not breathe vapour or spray.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P360	Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.
Environment & disposal	Do not allow to enter the sewer system, water bodies or soil. Only give completely emptied containers for recycling. Take liquid residues to a collection point for waste paint; dispose of dried residues as construction waste/waste paint (cured) or household waste.
Binding source	Label and safety data sheet CAIRCON Latex paint. Emergency: Poison Information Centre Erfurt, 24 h: +49 361 730730.