

Pure, cold-pressed natural linseed oil · solvent-free · penetrates deep into wood · for furniture, doors, beams (interior) and for priming/saturating (exterior)

 Brush · Cloth · Sponge Application	 approx. 0.1–0.2 l/m² Consumption per coat	 24–48 h dust-dry*	 +20 to +25 °C optimal	 Solvent-free 100 % natural oil
---	--	--	--	---

*Guide value at 20–25 °C / 40–60 % relative humidity — all drying times on page 2.

CAIRCON Linseed oil is a pure natural product from the flax or linseed plant, cold-pressed and solvent-free. It penetrates particularly deep into the wood, lines the pores and polymerises inside into an insoluble compound. Ideal as surface protection for furniture, doors, beams and panelling indoors, as well as for priming and saturating wood outdoors.

IMPORTANT – RISK OF SELF-IGNITION: Store oil-soaked materials (cleaning cloths, sponges, sanding dust, polishing pads) airtight in metal containers or in water. Make sure that no oil comes into contact with porous insulating materials — otherwise there is a risk of self-ignition due to the vegetable oil content. In the container and applied on its own, the oil is NOT self-igniting.

1 · PREPARE THE SUBSTRATE

- Clean the substrate**
Make sure the wood surface is dry, clean and pH-neutral. For stubborn dirt, pre-treat the surface with the **Special cleaner**.
- Sand**
Lightly sand the surface with fine sandpaper to create a smooth, even base for the oil application.
- Remove sanding dust**
Remove the sanding dust with a lint-free cloth or a soft brush.

For third-party products used in substrate preparation: check compatibility and the end result beforehand on a test area — we accept no liability for the result obtained with third-party products.

2 · APPLY THE OIL

- Application**
Apply the oil thinly with a high-quality brush, lint-free cloth or sponge and work it well into the surface. Spread evenly and avoid puddling; be sure to remove excess oil.
- Thinning (optional)**
To improve penetration, you can thin the oil with 20–50 % **Balsam turpentine oil** — this makes it easier to spread into corners and edges.
- Check drying**
Check progress with the finger test: the coat should be dust-dry and not tacky; visible glossy patches indicate still-wet areas.

3 · AFTERCARE & MAINTENANCE

- Further coats**
After the first coat has dried, apply 1–2 more coats depending on the desired level of protection; the intermediate drying varies, especially at low temperatures.
- Remove excess**
Avoid excess — after approx. 30 minutes, remove excess oil with a lint-free cloth until the surface appears evenly satin-matt.
- Coat too thick**
A coat applied too thickly that has already begun to dry can be removed with soda lye.

MAKE A TEST AREA: Before larger areas, make a test area and check adhesion and colour when dry — wood species react differently to oil coats.

TROCKENZEITEN

24–48 h DUST-DRY	2–4 days RECOATABLE	7–14 days FULLY DRY
----------------------------	-------------------------------	-------------------------------

Sufficient atmospheric oxygen is needed for drying — ensure good ventilation, e.g. with a fan.

All times apply at 20–25 °C and 40–60 % rel. humidity; other conditions change them.

PRODUCT DATA (GUIDE VALUES)

Colour	golden-yellowish
---------------	------------------

Base	100 % natural, cold-pressed linseed oil
Consumption	approx. 0.1–0.2 l/m ² per coat
Fields of use	untreated wood surfaces such as wooden tables, worktops, garden furniture, terraces, windows, furniture and doors
Application	with brush, cloth or sponge
Flash point	240 °C
Storage	always close the container tightly; without oxygen, light, contamination or frost the linseed oil keeps almost indefinitely

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS

Cleaning	Special cleaner
Tools	Brush set
Thinning	Balsam turpentine oil

SAFETY & DISPOSAL

Labelling	no hazard pictograms · no signal word — pure natural product, not subject to labelling under CLP
Risk of self-ignition	Store oil-soaked cloths, sponges and sanding dust only airtight in metal containers or in water; in the container and applied on its own not self-igniting.
Product odour	Owing to the natural raw materials used, a typical product odour may occur.
P101 / P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
Environment & disposal	Only give completely emptied containers to recyclables collection; dispose of dried oil residues via household waste, give liquid residues to the collection point for waste paint/waste oil.
Binding source	The label and safety data sheet CAIRCON Natural linseed oil apply.