

Processing instructions / Technical data sheet

CAIRCON - Boiled linseed oil

CAIRCON Linseed oil varnish offers solvent-free surface protection for all interior wood that is not subject to heavy wear, especially for furniture, doors, worktops, wall paneling and beams. It enhances the wood grain in a warm tone, is very economical and can be easily reworked locally if damaged.

It is also suitable as a primer for subsequent coats with opaque stand oil paints on untreated wood as well as for colored wood stains on highly absorbent or weathered wood.

Step 1: Preparing the surface

- Cleaning the surface:** Make sure that the wooden surface is dry, clean and pH-neutral. For stubborn stains, pre-treat the surface with our **CAIRCON - Special pre-cleaner** to achieve optimum results.
- Sanding the surface:** Lightly sand the surface with fine sandpaper to create a smooth and even base for the oil application.
- Remove the sanding dust with a lint-free cloth or a soft brush to clean the surface thoroughly.

If third-party products are used to prepare the substrate, their compatibility and the perfect final result must be checked by applying a test surface BEFORE coating. If third-party products are used, no liability can be accepted for a proper application result.

Step 2: Applying the linseed oil varnish

- Application methods:** Apply **CAIRCON** Linseed Oil Varnish thinly with a high-quality brush or a lint-free cloth or sponge and work it well into the surface. Take care to distribute the oil evenly and avoid puddles. Excess oil should always be removed.
- to improve the penetration behavior of the linseed oil varnish, it can be diluted with 20-50% **CAIRCON - Balsam turpentine oil** if necessary. This makes it easier to spread in corners and edges.
- Check the drying progress with the finger test:** The coating should be dust-dry and not stick to your finger. Visible shiny spots indicate that the coating is still damp.

Step 3: Aftercare and care

- Further coats:** After the first coat has dried, apply 1-2 further coats, depending on requirements and the desired degree of protection. The drying time between coats may vary, especially at lower temperatures.
- Avoid excess linseed oil varnish.** After approx. 30 minutes, remove excess linseed oil varnish with a lint-free cloth until the surface has an even, silky matt appearance.
- If a layer of W210 has been applied that is too thick and has already dried, it can be removed with caustic soda.

Drying time

Please note: these times only apply at an optimum air temperature of 20-25°C and humidity of 40-60% and may vary if these conditions change.

Dust-dry after 24 - 48 hours	paintable after 2 - 4 days	Fully dry 7-14 days
--	--------------------------------------	-------------------------------

This system requires sufficient oxygen in the air for drying. Good ventilation should therefore be ensured, for example by using a fan.

Technical data

Color	Golden-yellowish
Base	100% natural linseed oil varnish
Consumption	approx. 0.1 - 0.2 L/m ² (per coat)
Areas of application	untreated wooden surfaces such as wooden tables, worktops, garden furniture, terraces, windows, furniture and doors etc.
Processing	with brush, cloth, sponge
Flash point	240°C
Storage	Always close the container tightly. This oil can be stored almost indefinitely without oxygen, light, contamination or frost.

Safety and protective measures

Caution: Work materials soaked with **CAIRCON** linseed oil varnish, e.g. cleaning cloths, sponges, sanding dusts, polishing pads with oil that is not completely dry, should be stored in an airtight metal container or in water, and care should be taken to ensure that no oil comes into contact with porous insulating materials when spreading, as otherwise there is a risk of spontaneous combustion due to the vegetable oil content.

It is NOT self-igniting in containers and when used alone.

Store out of reach of children. Pay attention to possible allergies to natural substances. The natural raw materials used may cause a typical product odor.

Recommended additional products

Cleaning	CAIRCON - Special pre-cleaner
Tools	CAIRCON - Brush set
Dilution	CAIRCON - Balsam turpentine oil