

 Brush · Roller · Airless Application	 approx. 10 m²/l per coat (2× recomm.)	 approx. 1 h touch-dry*	 above +10 °C Application	 Water-based max. 10 % water
--	--	--	--	---

*Guide value at 20–25 °C / 40–60 % relative humidity — all drying times on page 2.

CAIRCON High-build wood stain is a weather-resistant, decorative water-based wood stain for exterior and interior use. It offers optimum brushing properties and is suitable for all non-load-bearing wooden components made of hardwood or softwood, including tropical wood species — ideal for wooden beams, roof soffits, cladding, formwork, tables, chairs, gates, fences, wooden walls, garden houses, window frames, doors and cabinets.

IMPORTANT — CHECK THE COLOUR: Check the colour **BEFORE** application with a test coat — after application, complaints and exchanges are excluded. Only paint contiguous areas with material from the same delivery / batch number; this also applies to touch-ups (same consistency, same batch, same tool).

1 · PREPARE THE SUBSTRATE

1	Clean Remove loose paint parts as well as non-adhering old coatings and coverings and clean afterwards (mechanically or with a suitable paint stripper).
2	Degrease (if needed) For greasy, oily or soiled surfaces, pre-treat with the Special degreaser : spray on, leave to act for 3–5 minutes, work with a cloth or brush, rinse with clean water and allow to dry completely. The substrate must be clean, dry and free of grease.
3	Roughen Roughen the surface with sandpaper or a sanding sponge.

For third-party products used in substrate preparation: check compatibility and the final result beforehand on a test area — we accept no liability for the result obtained with third-party products.

2 · APPLY THE STAIN

4	Application Apply with brush, roller (Floor roller) or airless sprayer. For optimum adhesion, first apply a thin preliminary coat; work wet-in-wet, apply evenly at the specified coverage and back-roll crosswise. Stir well before use.
5	Thinning The stain is supplied ready to use and needs no thinning; if required, thin with up to 10 % water.
6	Temperature conditions Only apply above +10 °C. At low temperatures/high humidity the properties are reached with a delay; at high temperatures/low humidity the stain dries too quickly. During application and drying, protect surfaces from rain, wind, direct sunlight and dew.

MAKE A TEST AREA: Before larger areas, make a test area and check adhesion, compatibility and colour with the substrate when dry.

TROCKENZEITEN

1 h TOUCH-DRY	4 h RECOATABLE	7 days FULLY CURED
-------------------------	--------------------------	------------------------------

Double coat recommended.

All times apply at 20–25 °C and 40–60 % relative humidity; other conditions change the times.

PRODUCT DATA (GUIDE VALUES)

Gloss level	satin
Base	water-based
Coverage	approx. 10 m ² /l per coat (double coat recommended)
Application area	wood interior & exterior — non-load-bearing components of hardwood/softwood and tropical wood (beams, cladding, fences, doors, windows, etc.)
Application	with roller, brush or sprayer · only above +10 °C
Thinning	ready to use · optionally up to 10 % water
Storage	approx. 24 months unopened at +5 to +25 °C, protected from frost and moisture; keep container tightly closed

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS

Cleaning	Special degreaser
Tools	Floor roller · Brush set
Similar products	Wood topcoat

SAFETY & DISPOSAL

Labelling	Hazard pictogram GHS09 (environmental hazard) · signal word: Warning
Hazard statements (H)	H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
Precautionary statements (P)	P273 Avoid release to the environment. P391 Collect spillage. P501 Dispose of contents/container to a suitable recycling or disposal facility.
Binding source	Label and safety data sheet CAIRCON High-build wood stain apply.