

 Brush · Cloth · Sponge Application	 approx. 0.1–0.2 l/m² Coverage per coat	 24–48 h touch-dry*	 +20 to +25 °C optimal	 Solvent-free 100 % natural oil
--	--	--	---	--

*Guide value at 20–25 °C / 40–60 % relative humidity — all drying times on page 2.

CAIRCON Furniture oil is used for the decorative treatment and renovation of wooden furniture. It is suitable for the maintenance and initial treatment of hardwood and softwood, penetrates deeply, cures abrasion-resistant and preserves the wood structure. The solvent-free oil can be used indoors and outdoors.

IMPORTANT – RISK OF SPONTANEOUS COMBUSTION: Store oil-soaked materials (cleaning cloths, sponges, sanding dust, polishing pads) airtight in metal containers or in water. Make sure that no oil comes into contact with porous insulating materials — otherwise, due to the vegetable-oil content, there is a risk of spontaneous combustion. In the container and once applied on its own, the oil is NOT liable to spontaneous combustion.

1 · PREPARE THE SUBSTRATE

1	Clean the substrate Make sure the wood surface is dry, clean and pH-neutral. For stubborn dirt, pre-treat the surface with the Special cleaner .
2	Sand Lightly sand the surface with fine sandpaper to create a smooth, even base for the oil application.
3	Remove sanding dust Remove the sanding dust with a lint-free cloth or a soft brush.

For third-party products used in substrate preparation: check compatibility and the final result beforehand on a test area — we accept no liability for the result obtained with third-party products.

2 · APPLY THE OIL

4	Application Apply the oil thinly with a high-quality brush, lint-free cloth or sponge and work it well into the surface. Spread evenly and avoid puddling; be sure to remove any excess oil.
5	Thinning (optional) To improve penetration, you can thin the oil with 20–50 % Balsam turpentine oil — this makes it easier to spread into corners and edges.
6	Check the drying Check progress with the finger test: the coat should be touch-dry and not tacky; visible shiny spots indicate areas that are still wet.

3 · AFTERCARE & MAINTENANCE

7	Further coats Once the first coat has dried, apply 1–2 further coats depending on the desired level of protection; the intermediate drying time varies, especially at low temperatures.
8	Remove excess Avoid excess — after approx. 30 minutes, wipe off surplus oil with a lint-free cloth until the surface appears evenly satin-matt.
9	Layer too thick A layer applied too thickly that has already begun to dry can be removed with soda lye.

MAKE A TEST AREA: Before larger areas, make a test area and check adhesion and colour when dry — wood species react differently to oil coatings.

TROCKENZEITEN

24–48 h TOUCH-DRY	2–4 days RECOATABLE	7–14 days FULLY DRY
-----------------------------	-------------------------------	-------------------------------

Sufficient atmospheric oxygen is needed for drying — ensure good ventilation, e.g. with a fan.

All times apply at 20–25 °C and 40–60 % relative humidity; other conditions change the times.

PRODUCT DATA (GUIDE VALUES)

Colour	golden-yellowish
Base	100 % natural, cold-pressed linseed oil
Coverage	approx. 0.1–0.2 l/m ² per coat
Application areas	untreated wood surfaces such as wooden tables, worktops, garden furniture, decking, windows, furniture and doors
Application	with brush, cloth or sponge
Flash point	240 °C
Storage	Always keep the container tightly closed; without oxygen, light, contamination or frost, the furniture oil keeps almost indefinitely.

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS

Cleaning	Special cleaner
Tools	Brush set
Thinning	Balsam turpentine oil

SAFETY & DISPOSAL

Labelling	no hazard pictograms · no signal word — pure natural product, not subject to labelling under CLP
Risk of spontaneous combustion	Store oil-soaked cloths, sponges and sanding dust only airtight in metal containers or in water; in the container and once applied on its own, not liable to spontaneous combustion.
Product odour	The natural raw materials used may give rise to a typical product odour.
P101 / P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
Environment & disposal	Only give completely emptied containers for recycling; dispose of dried oil residues with household waste, and liquid residues at the collection point for waste paint/waste oil.
Binding source	Label and safety data sheet CAIRCON Furniture oil apply.