

 Brush · Roller · Sprayer Application	 150–200 ml/m² Coverage depending on absorbency	 approx. 6 h recoatable*	 from +5 °C Application	 Water-based Clean with water
--	---	---	--	--

*Guide value at 20–25 °C / 40–60 % relative humidity — all drying times on page 2.

CAIRCON Wood primer is a high-quality, solvent-free and breathable primer for wood in interior and exterior areas. It regulates the absorbency of the wood, protects against moisture and provides very good substrate consolidation — low-odour, drying transparent and with high penetration depth for optimum adhesion of subsequent water-based topcoats. Particularly suitable for softwoods such as pine, spruce and fir without ground contact (carports, fences, garden houses, etc.).

IMPORTANT — NO GLOSS: Make sure that no gloss forms on the surface during application and drying, so that subsequent coatings adhere well.

1 · PREPARE THE SUBSTRATE

- Clean the substrate**
The substrate must be firm, clean, sound and dry. Before application, remove residues such as dust, dirt, oil or other adhesion-reducing materials and carefully protect surfaces that are not to be treated.

2 · APPLY THE PRIMER

- Application**
Apply the primer with roller, brush or sprayer. Make sure that no gloss forms during application and drying. The topcoat can be applied after approx. 6 hours.
- Application temperature**
The application temperature for substrate and air should be at least +5 °C to ensure optimum drying conditions.

DRIES TRANSPARENT: The primer is milky-white and dries colourless (transparent); it serves as a protective and bonding primer, not as a topcoat.

TROCKENZEITEN

approx. 6 h

RECOATABLE

Value as a guide; the drying time varies with temperature and the absorbency of the substrate.

PRODUCT DATA (GUIDE VALUES)

Gloss level	satin-matt
Colour tone	milky-white, dries colourless (transparent)
Binder base	acrylic dispersion (solvent-free)
Coverage	approx. 150–200 ml/m ² depending on the absorbency of the substrate
Application area	wood in interior and exterior areas (softwoods without ground contact)
Application	with roller, brush or sprayer · from +5 °C
Drying time	recoatable after approx. 6 h
VOC content	EU limit value (cat. h) 30 g/l VOC (2010); this product max. < 1 g/l VOC
Storage	18 months unopened in the original container

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS

Topcoat	Wood topcoat
Tools	Floor roller · Paintbrush set

SAFETY & DISPOSAL

Labelling	no hazard pictograms · no signal word — not subject to labelling under CLP
-----------	--

Supplemental hazard information	none
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.