

				
Roller · Trowel Application	approx. 1–2 kg/m² Consumption	approx. 12 h recoatable*	min. +5 °C Application	Water-based Clean with water

*Guide value depending on layer thickness and substrate — drying times on page 2.

Brushable plaster is a decorative, fine-grained brushable plaster for interior use — ideal for the individual and seamless design of walls and ceilings. It offers a matt surface and, thanks to its easy-to-work formula, can be applied effortlessly with a roller or trowel. Its versatile design options enable creative designs for any room, from the living room and bedroom to the kitchen and bathroom.

PREPARE THE SUBSTRATE: The substrate must be clean, dry, free of dust and grease as well as load-bearing and firm. Completely remove loose or flaking paint layers, chalking coatings, distemper paints, cement laitance, lime deposits, non-adhering wallpaper and release-agent residues.

1 · PREPARE THE SUBSTRATE

1	Clean & smooth Lightly sand glossy old coatings or pre-treat with a degreasing cleaner to improve adhesion. Pre-treat sanding and strongly absorbent substrates with Deep primer . Carefully level and smooth cracks, holes and unevenness with filler.
2	Pre-priming A base coat with Render primer is recommended to ensure uniform adhesion and a perfect result.

2 · APPLY THE BRUSHABLE PLASTER

3	Prepare the material Stir thoroughly before application. If required, thin with up to 10 % water to achieve the desired consistency.
4	Apply & texture Apply evenly with a roller or trowel. Create decorative textures with a texture roller, sponge or other tools while the plaster is still wet.

MAKE A TEST AREA: Before larger areas, check the texture and result on a test area.

TROCKENZEITEN

approx. 12 h

RECOATABLE

Application temperature at least +5 °C (substrate and surroundings) during application and drying.

The time is a guide value and changes with temperature and humidity.

PRODUCT DATA (GUIDE VALUES)

Binder base	styrene-acrylate dispersion
Pigment base	titanium dioxide, various fillers and quartz sand
Gloss level	matt
Colour	white
Consumption	approx. 1–2 kg/m ² (depending on layer thickness and substrate)
Application	at least +5 °C (substrate and surroundings) · brushing or rolling
Thinning	water (max. 10 %)
Storage	dry, cool, frost-free

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS

Cleaning	Etching solution · Special pre-cleaner
Substrate	Deep primer · Render primer · Levelling compound
Tools	Texture roller · Brush · Roller · Trowel

SAFETY & DISPOSAL	
Labelling	no hazard pictograms · no signal word · no hazard statements — not subject to labelling under CLP
P260 / P264 / P280	Do not breathe dust/mist/spray. Wash hands thoroughly after use. Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 / P363	If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse.
Environment & disposal	Do not allow to enter drains, waterways or soil. Only give completely emptied containers for recycling; dried product residues as construction waste.