

 Thinning · cleaning · degreasing Application	 5–10 % Dosage for thinning	 clean immediately after work	 +5 to +25 °C Storage, away from ignition sources	 Highly flammable H225 · not for water-based
--	--	--	--	---

WARNING highly flammable (GHS02, H225) and eye-irritating (H319): keep away from ignition sources, no smoking, wear protective gloves/eye protection, ventilate well. Not suitable for water-based products.

CP910 Universal thinner is optimal for thinning CAIRCON products such as Metal protection lacquer, Boat varnish, Window & door lacquer and Metal roof paint, as well as for many solvent-based systems (synthetic-resin, alkyd-resin and oil-based lacquers and glazes). Dosage 5–10 % depending on the desired consistency — especially for spray applications or the first coat. Not suitable for water-based products.

IMPORTANT — HIGHLY FLAMMABLE: Liquid and vapour are highly flammable (H225). Keep away from heat, hot surfaces, sparks, open flames and ignition sources, do not smoke and take measures against electrostatic charges. Ensure sufficient ventilation and wear suitable protective clothing, gloves and eye protection.

1 · APPLICATION

1	Thinning To thin solvent-based lacquers/glazes, add 5–10 % depending on the desired consistency — especially recommended for spray applications or the first coat with roller/brush. Not for water-based products.
2	Cleaning tools Clean brushes, rollers and spray equipment immediately after work with the thinner; reliably removes fresh paint residues. For dried-on lacquers, allow a longer soaking time.
3	Degreasing Suitable for degreasing metallic surfaces before painting — removes oil, grease, release agents and contaminants. Then wipe dry with a lint-free cloth and let flash off well.

TEST AREA ON SENSITIVE SUBSTRATES: On sensitive or coated substrates (e.g. old coatings, plastics) and with third-party products, test beforehand on a test area.

TROCKENZEITEN

5–10 %

DEPENDENT ON CONSISTENCY

Especially recommended for spray applications and the first coat.
Not suitable for water-based products.

PRODUCT DATA (GUIDE VALUES)

Suitability	CAIRCON Metal protection lacquer, Boat varnish, Window & door lacquer, Metal roof paint · synthetic-resin, alkyd-resin and oil-based lacquers/glazes
Dosage	5–10 % depending on the desired consistency
Further functions	tool cleaning · degreasing of metallic surfaces
Not suitable for	water-based products
Storage	+5 to +25 °C in tightly closed containers; protect from direct sun and ignition sources, keep out of reach of children
Disposal	product residues and contaminated containers as hazardous waste according to local regulations; do not allow to enter the environment/drains

All data are non-binding guide values and depend on substrate, tool and ambient conditions — no assured properties.

RECOMMENDED COMPLEMENTARY PRODUCTS

Compatible lacquers	Metal protection lacquer 4in1 · Boat varnish · Window and door lacquer
Tools	Paintbrush set · Floor roller

SAFETY & DISPOSAL

Labelling	GHS02 (flame) + GHS07 (exclamation mark) · signal word Danger — subject to labelling under CLP.
------------------	---

H225 / H319 / H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
P210 / P243	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources, no smoking. Take action to prevent static discharges.
P280 / P271 (added)	Wear protective gloves and eye protection. Use only outdoors or in a well-ventilated area (formalised from the body-text notes of the original).
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes, remove contact lenses if present and easy to do, continue rinsing.
Environment & disposal	Product residues and contaminated containers as hazardous waste via the hazardous-waste collection point; not into the environment/drains. Waste code EWC 08 01 11* (solvent-containing).
Binding source	Label and safety data sheet CP910 Universal thinner. Emergency: Poison Information Centre Erfurt, 24 h: +49 361 730730.