

Instructions for Use / Technical Data Sheet

CAIRCON - Masonry Primer

Product Description

Masonry primer for strengthening and priming sanding, porous and highly absorbent mineral substrates such as render, concrete and masonry. Owing to its high penetration depth, the primer is particularly suitable for our roof coating. Masonry primer is easy to apply, reduces and equalises substrate absorbency and is therefore the optimum substrate pretreatment.

Substrate Preparation

Substrates must be sound, clean, dry and free of grease. Wash chalking substrates with a pressure washer. First treat heavily soiled substrates with Special Pre-Cleaner.

If products from third-party manufacturers are used for substrate preparation, their compatibility and a satisfactory final result must be verified by preparing a test area BEFORE coating. No liability can be accepted for proper application results when third-party products are used.

Application Instructions:

Stir well before use. Do not apply below +5°C. Apply undiluted and evenly with a brush, surface brush or ceiling brush. Treat the substrate until it is saturated and no longer absorbs primer. Do not spray with airless equipment. Do not mix with other products. After drying, no glossy film should be visible on the substrate. Clean tools immediately after use with warm water and household cleaner.

Technical Data

- Composition: Special synthetic dispersion, water, additives, preservatives
- Colour: Colourless
- Form supplied: Liquid
- pH value: approx. 7
- Recoatable: after approx. 10-12 hours
- Coverage: approx. 7m²/L

Warning and Safety Information

Hazard pictograms: Not required

Signal word: None

Hazard statements: None

Supplemental hazard information: None

Safety Instructions:

- **P101** If medical advice is needed, have product container or label at hand.
- **P102** Keep out of reach of children.

Recommended Additional Products

Cleaning	CAIRCON - Special Cleaner
Pretreatment for:	CAIRCON - Roof Paint

