

Application Instructions / Technical Data Sheet

CAIRCON - Floorboard Varnish

Product description

Universal solvent-based varnish for interior and exterior areas.

The varnish is particularly scratch-resistant, abrasion-resistant and durable. Ideally suited for wooden floors, furniture, doors, panels and other heavily used wood surfaces.

Substrate preparation

The surface must be clean, dry, sound and free from grease, wax, salt, glue and dust.

Sand old coatings and remove loose varnish residue.

When using cleaners or preparation products from other manufacturers, test their compatibility by applying a test coat.

A test coat is recommended to test colour and adhesion on the relevant substrate.

Application

Stir the varnish well before application (do not shake).

Application can be carried out with a brush, paint roller (e.g. mohair or flock roller) or airless spray equipment (minimum 180 bar).

Fine intermediate sanding (approx. 240 grit) should be carried out between coats to achieve an even result.

Work wet-on-wet on larger surfaces to avoid lap marks.

Note:

Check colour accuracy with a test coat BEFORE application; no complaints or exchanges are possible after application. On continuous surfaces, use only colours from the same delivery or with an identical batch number. Repairs to a surface must also use material and tools with the same consistency and batch number.

Drying times (at 20-25°C, 40-60% relative humidity):

- Dust dry: after approx. 4 hours
- Recoatable: after approx. 12 hours
- Fully cured: after approx. 7-10 days. Do not subject the coated surface to loads or cover it during this time.

Warnings and safety information

Hazard pictograms:



GHS07
Exclamation mark



GHS02
Flame

Signal word: Danger

Hazard statements for physical hazards:

H225 Highly flammable liquid and vapour.

Hazard statements for health hazards:

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Hazard statements for environmental hazards:

H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements - Disposal:

P501 Dispose of contents/container at a suitable recycling or disposal facility.