

# Pin Squeegee for Floor Coating

## Product Designation

Pin squeegee for applying epoxy resin, floor coatings and self-leveling compounds.

## Intended Use

The pin squeegee is used **for the even distribution and** smoothing of liquid and self-leveling floor coatings such as **epoxy resin, fillers and leveling compounds** on flat floor surfaces.

The product is intended for hand-held use.

## Assembly

1. Check the pin squeegee for visible damage.
2. Insert a suitable handle (e.g. telescopic handle, depending on the set variant) securely into the handle holder.
3. Fix the connection securely (check lock/twist lock).
4. Check for tight fit before starting work.

## Application

1. Mix the coating material according to the manufacturer's instructions.
2. Apply the material to the floor in sections.
3. Guide the pin squeegee over the surface with even pressure.
4. Work in straight lanes to achieve an even layer thickness.
5. Avoid overlaps to prevent material accumulation.

**Note:** The teeth height of the squeegee determines the layer thickness.

## Cleaning and Maintenance

1. Clean the squeegee immediately after use.
2. Remove fresh material with a suitable cleaning agent.
3. Mechanically remove dried residues carefully.
4. Allow to dry after cleaning.
5. Store in a dry and frost-free place.

## Safety Instructions

⚠️ **Risk of injury from sharp edges.** The metal teeth of the pin squeegee can be sharp. Wear protective gloves when working.

⚠️ **Risk of slipping.** There is a risk of slipping when working on freshly coated surfaces. Use non-slip work shoes or suitable spiked shoes.

⚠️ **Not a toy.** The product is not suitable for children. Keep out of reach of children.

⚠️ **Intended use. Only use** the pin squeegee for its intended purpose. Do not use as a lever, tool replacement or carrying aid. Do not use for dry, abrasive or sharp-edged materials.

