

Application Instructions / Technical Data Sheet

CP910 - Universal Thinner

Use as a thinner

- Ideal for thinning CAIRCON products such as metal protection paint, boat/yacht varnish, window and door paint and metal roof paint.
- Also suitable for many solvent-based systems: synthetic resin, alkyd resin and oil-based paints, varnishes and stains.
- **Dosage: 5-10%** depending on the required consistency. Particularly recommended for spray applications or the first coat applied with a roller/brush.

Warning: Not suitable for water-based products. When used with third-party products, test on a sample **area** beforehand.

Cleaning tools and equipment

- Clean brushes, rollers and spray equipment with Universal **Thinner immediately** after work.
- Reliably removes fresh paint residue.
- A longer contact time is required for dried paints and varnishes.

Degreasing substrates

- Suitable for degreasing metal surfaces before painting.
- Reliably removes oil, grease, release agents and other contaminants.
- Then rub dry with a lint-free cloth and allow to air thoroughly.

Warning: For sensitive or coated substrates (e.g. old coatings, plastics), test on a sample area beforehand.

Packaging and storage

Store in tightly closed containers at temperatures between 5°C and 25°C. Protect from direct sunlight and ignition sources. Keep out of reach of children.

Disposal

Dispose of product residues and contaminated containers as hazardous waste in accordance with local regulations. Avoid release to the environment.

Warnings and safety information

Hazard pictograms:



GHS07
Exclamation mark



GHS02
Flame

Signal word: Danger

Hazard statements:

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Precautionary statements - Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243: Take action to prevent static discharges.

Precautionary statements - Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental hazard statements:

EUH066: Repeated exposure may cause skin dryness or cracking.

Wear suitable protective clothing and gloves. Ensure adequate ventilation. Do not allow to enter drains.

CAIRCON