# Processing instructions / technical data sheet

## **CAIRCON - Tile paint primer**

### **Product description**

This primer is a solvent-free special primer based on polymer dispersion to optimize the adhesion of Tile Varnish and 2K Tile Varnish and others commercial tile paints.

## **Application** areas

This tile primer acts as a bonding agent on ceramic and mineral tiles. It can be used indoors and outdoors, on floors or walls.

# Substrate preparation

When applying **tile primer**, the tile surface must be absolutely free of grease and other dirt. For thorough pre-cleaning, we recommend using our **special pre-cleaner**. For optimal adhesion, sand the surface with fine sandpaper (180-240 grit). Old coatings must be removed before coating. Glazed tiles and tiles with a special coating (beading effect) must always be sanded thoroughly before coating so that this coating is removed without leaving any residue, otherwise serious adhesion problems can occur.

## **Technical specifications**

Drying time: approx. 1-2 hours (at 20°C / 50% relative humidity)
Tools: Lambskin roller, foam roller or brush
Yield: approx. 5m²/L'
Water and solvent free
Suitable for indoor and outdoor, wall and floor

### **Processing instructions**

Stir well before use. Do not process below +5°C. Apply undiluted evenly with a brush, brush or roller. The substrate should be treated until it is saturated and no longer absorbs the primer. Do not spray with an airless device. Must not be mixed with other products. Clean tools immediately after use with warm water and a household cleaner.

### **Security and Protection Measures**

Keep out of the reach of children. Store dry, well shot and cool, but not below +5°C. Ensure sufficient stability during transport. The usual protective measures must also be observed when using low-emission paint and varnish. Ensure adequate ventilation during processing and drying. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, water bodies or soil. Only empty containers for recycling.

# Recommended additional products

2K Tile paint Tile Varnish Special pre-cleaner